

Amendments to the Specification

Please replace the third full paragraph on page 5, beginning line 11, with the following amended paragraph:

--As seen in Figs. 3 and 4, in brief, the construction of the headrest frame assembly (HF) is such that a rotatable vertical support frame member (20) of generally "U" shape is biasingly and rotatably connected with a horizontal frame section (11) of a base frame member (1) of generally "inverted U" shape via a pair of first and second rotary frame pieces (21) (22) and a frontal cover frame piece (23) fixed to frame member (20).--

Please replace the fifth full paragraph on page 5, beginning line 24, with the following amended paragraph:

--Fixed respectively to the first and second rotary frame pieces (21) (22) are two end portions ~~(20a)~~ ~~(20a)~~ (20e) (20e) of the vertical frame member (20) in such a manner as to extend ~~downwardly~~ downwardly therefrom.--

Please replace the last paragraph on page 6, bridging page 7, with the following amended paragraph:

-- As viewed from Fig. 5 in conjunction with Fig. 3, the two stay portions (10) of base frame member (1) are slidably inserted through a stay holder (50) fixed in the top of seat back (SB), such that, within the seat back (SB), one

of the two stay portions (10) or the right-side stay portion (10) is provided with a biasing spring (30) for the purpose of biasing the base frame member (1) in upward direction. As shown, the ~~basing~~ biasing spring (30) is securely connected between a bracket (40) integral with the seat back (SB) and a securing lug (16) fixed to the right-side stay portion (10).--